

# BIG BLUE MP GREASE 2



This premium MP lithium complex grease has been formulated to withstand a vast range of operating temperatures (-40°C to 204°C) while providing protection and water washout resistance. An outstanding wide temperature range grease that provides exceptionally low start up resistance and prevents bearing leakage at higher temperatures. This grease contains superior rust and corrosion protection of moving parts under extreme pressure while providing excellent shock load ability and water resistance. This grease is also very well known for being an exceptional grease for most sealed-for-life bearings as well.

<b>NLGI GRADE</b>	<b>BIG BLUE</b>
Penetration @ 25°C (77°F), Worked 60 Strokes	265 - 295
Soap Type	Lithium Complex
Soap Content, %	8.8
Dropping Point, °C (°F)	260°C (500+°F)
Base Oil Viscosity CST @ 40°C	175
Base Oil Viscosity CST @ 100°C	12
Weight, lbs per Gallon	7.74
Colour	Blue
Appearance	Buttery
Timken OK Load, lbs	40 lbs
Rust Prevention	Pass
*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES	

Applications: Meets or exceeds the following service requirements:

- The adhesive and water washout resistant properties make this an optimal chassis lubricant for on and off road equipment in agriculture, construction, logging, trucking, and mining services where demanding washing or shock loading protection is needed. This formulation is also recommended for electric motors of the NEMA insulation class A & A types.
- Recommended for disc brake and chassis applications, 5th wheels, u-joints and steering linkage. Also advised for all types of ball bearings including plain, heavy loaded, journal, needle and ball and roller.
- NLGI certified GC-LB in wheel bearing and chassis applications and meets the highest performance GC-LB categories for dual service.