

DIESEL ENGINE OIL CK-4



CANADA GOLD HEAVY DUTY DIESEL ENGINE OIL is developed to meet the latest EPA On-Highway Exhaust Emission Standards which require significant reductions in nitrogen(Nox) and particulate matter(PM) and maximum chemical limits on sulfated ash(SA), phosphorus(P), and Sulphur(S) to address the emissions system compatibility and durability standards. Our diesel engine oil meets the industries latest CK-4 specification. Diesel Engine Oils are available in 10W30 and 15W40.

SAE GRADE	15W40
Density (D4052) kg/m@ 15°C	
Kinematic Viscosity (D445):	
cSt @ 40°C	118.5
cSt @ 100°C	15.7
Viscosity Index (D2270)	141
Viscosity Cp CCS	6300 @ -20°C
Viscosity Cp MVR TP1	19000 @ -25°C
Flash Point (D92), °C	236
Pour Point (D97), °C	-33
Specific Gravity 15.6°C (60°F)	0.871
Ash Sulphate, mass%	0.98%
*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES	

Applications: Meets or exceeds the following service requirements:

- > API: SM, SL, SJ, SH
- > ACEA: E7
- > CATERPILLAR: ECF-1a, ECF-2, ECF-3
- > CUMMINS: CES 20081
- > DETROIT DIESEL: 93K218
- > MACK: EO-O Premium Plus '07
- > MAN: M3275
- > MB APPROVAL: 228.3, 228.31
- > MTU: Type2
- > VOLVO: VDS 4T