

SYNTHETIC GAS ENGINE OIL



CANADA GOLD SYNTHETIC ENGINE OILS are formulated to meet the latest car manufacturer's warranty requirements and designed to meet the demands of small displacement, high RPM fuel efficient engines found in today's domestic and foreign automobiles. A blend of high quality synthetics and specialized additives provide maximum protection against high temperature oxidation, wear, rust, corrosion, viscosity breakdown while keeping your engine exceptionally clean and free of sludge and varnish.

SAE GRADE	0W20	5W20	5W30	10W30
Density (D4052) kg/m@ 15°C				
Kinematic Viscosity (D445):				
cSt @ 40°C	44.8	52.5	58.2	63.6
cSt @ 100°C	8.6	9	10.5	10.7
Viscosity Index (D2270)	175	156	173	155
CCS Viscosity (D2602):				
cP @ -35°C				
cP @ -30°C				
cP @ -25°C				
Flash Point (D92), °C	230	232	234	235
Pour Point (D97), °C	-49	-45	-43	-40
Colour (ASTM)				
Ash Sulphate, mass%				
*NOTE: VALUES SHOWN ABOVE ARE REPRESENTATIVE OF CURRENT PRODUCTION AND MAY VARY WITHIN MODEST RANGES				

Applications: Meets or exceeds the following service requirements:

- Recommended passenger vehicles, light duty pick ups, motorcycles and other gasoline engines.
- Recommended for domestic and foreign high performance engines, especially small high RPM and turbo charged engines
- Exceeds API service classification SN - Exceeds ILSAC GF-5 requirement
- Meets and exceeds the requirements for: GM 6094M, Chrysler MS-6395 N, Ford WSS-M2C 929-A, WSS-M2C 9306-A, WSS-M26946-A, General Motors requiring Dexos I

*Not recommended for heavy duty critical truck engines

MEETS OR EXCEEDS EXPECTATIONS